



Pressure transducer EDI

**Pressure range up to 16 bar
for panel board mounting
Output signal: 4 - 20 mA**

Electronic pressure transducer with integrated relative pressure sensor for panel board mounting, quick-connect for pneumatic tube, analogue output 4 to 20 mA and operating voltage 12...30 V-DC.
Function: the device converts the pressure applied to the sensor into a proportional DC-current (2 - wire technology).

Type overview EDI

| Order reference | Measuring range (bar)* | Max. perm. pressure (bar) | Max. inaccuracy at 25° C | Operating voltage U _B (V-DC) | Part No. |
|-----------------|------------------------|---------------------------|--------------------------|---|----------|
| EDI 10 | 0 - 10 | 25 | 2,5 % | 12...30 | 260219 |
| EDI 16 | 0 - 16 | 25 | 2,5 % | 12...30 | 260226 |

*4 mA = 0 bar / 20 mA = measuring range end value

Technical Data EDI

| Technical operating data | |
|--|----------------------|
| Permissible operating voltage range | ± 10 % |
| Operating voltage influence at ± 10% operating voltage fluctuation | < 0.1% |
| Duty factor ED | 100% |
| Permissible ambient and media temperature | -20° C up to + 60° C |
| Permissible ambient humidity to rel. humidity, non-condensing | 10% up to 90% |
| Permissible storage temperature | -40° C up to + 80° C |
| Clearance and creepage distances | VDE 0110 |
| Working position | any position |
| Power consumption | max. 1 VA |

| Pressure connection | |
|---------------------------------------|--------------------|
| Quick-connect suitable pneumatic tube | 6 x 1 mm Festo PAN |

| Output signal | |
|-----------------|-----------|
| Analogue output | 4 - 20 mA |

| Enclosure | |
|--------------------------|--|
| Material | RABS flameproof, UL-approved |
| Mounting | snap on 35 mm DIN-rail connector acc. to EN 50 035 |
| Enclosure-protection | IP 40 |
| Protection against shock | acc. VBG 4 |
| Terminals | Cage clamps |
| Cross section | 2,5 mm ² |
| Weight | 85 g |

Dimensions- / Circuit Diagrams EDI

