

CATERTEMP® PLUS WATERPROOF THERMOMETER

- Extruded aluminium case for superior durability
- Supplied complete with food penetration probe
- Colour-coded rubber bumper seals
- Meets the European Standard EN 13485

The CaterTemp Plus hand held thermometer is housed in a robust extruded aluminium waterproof case, offering IP66/67 protection, with a white anti-bacterial/salt resistant powder coated finish. The instrument incorporates the latest microprocessor technology with improved durability, designed for reliability and ease of use in day-to-day catering and food processing applications.

The CaterTemp Plus thermometer measures temperature over the range of -49.9 to 299.9 °C with a 0.1 °C resolution. The instrument features a large, easy to read, LCD display with open circuit and low battery indication. The unit is powered by a 9 volt PP3 battery which gives the thermometer approximately 5000 hours continuous use.

The on/off button is conveniently located at the front of the instrument as is the display hold facility. The CaterTemp Plus thermometer incorporates a secure battery compartment with a waterproof cover.

Each CaterTemp Plus thermometer is supplied with a permanently attached, water resistant, heavy duty, food penetration probe with a Ø3.3 x 130 mm stainless steel stem and one metre PU coiled lead. The probe is both strong, versatile and suitable for a variety of applications including liquids, semi-solids and granular materials.

- **Colour-coded rubber bumper seals**

The CaterTemp Plus thermometer is available with colour-coded rubber bumper seals that can help avoid cross-contamination - see below for details.

OPTIONAL ACCESSORIES:

- Acrylic wall bracket - screws not supplied (832-150)
- Protective black PVC boot (830-242)
- Anti-bacterial wipes - see page 35



FOOD PROCESSING



Order code	Description
221-056	CaterTemp Plus - black seal
221-256	CaterTemp Plus - yellow seal
221-356	CaterTemp Plus - green seal
221-456	CaterTemp Plus - red seal
221-556	CaterTemp Plus - blue seal
830-242	Protective PVC boot - black
832-150	Acrylic wall bracket

Specification	CaterTemp Plus
Range	-49.9 to 299.9 °C
Resolution	0.1 °C
Accuracy	±0.4 °C ±0.1 % of reading
Battery & life	9 volt PP3 alkaline - 5000 hours
Sensor type	K thermocouple
Display	12 mm LCD
Dimensions	35 x 60 x 115 mm
Weight	286 grams

FREE traceable certificate of calibration included