

SJE HI TEMP MASTER™ Pump Switch

Mechanically-activated, wide-angle switch specifically designed for performance and dependability in high temperature sump applications up to 200°F (93°C).

This mechanically-activated, wide-angle pump switch provides automatic control of pumps in:

- Water
- Sewage applications

This SJE HiTempMaster™ pump switch is not sensitive to rotation or turbulence allowing it to be used in both calm and turbulent applications.



Patent Pending

FEATURES

- Mechanically-activated, snap action contacts.
- High impact, corrosion resistant, polypropylene float housing.
- Adjustable pump range of 8 to 36 inches (20 to 91 cm).
- Twin wall design of float housing (patent pending) protects internal components from heat and moisture.
- CSA Certified.
- Five-year limited warranty.



LR54245



OPTIONS

This switch is available:

- for pump down applications.
- with a 125 VAC or 250 VAC piggy back plug.
- without a plug for direct wiring in 125 VAC or 250 VAC applications.
- in standard cable lengths of 10, 20, or 30 feet and 3, 6, or 10 meters (longer lengths available).

Ordering Information

| RBS Stock Code Pump Down | Description |
|-----------------------------|--|
| 3710000 | Hi Temp Master, 2-wire, 3mtr, No Plug |
| 3710010 | Hi Temp Master, 2-wire, 6mtr, No Plug |
| 3710014 | Hi Temp Master, 2-wire, 10mtr, No Plug |

SPECIFICATIONS

CABLE: flexible 16 gauge, 2 conductor (UL, CSA) SJOOW, water-resistant, (CPE)

FLOAT: 3.18 inch diameter x 5.58 inch long (8.1 cm x 14.2 cm), high impact, corrosion resistant, polypropylene housing for use in water up to 200°F (93°C)

MAXIMUM WATER DEPTH: 33 feet (10 meters) or 13 PSI (90 kPa)

ELECTRICAL:

125 VAC 50/60Hz Single Phase:

Maximum Pump Running Current:

13 amps

Maximum Pump Starting Current:

78 amps

250 VAC 50/60Hz Single Phase:

Maximum Pump Running Current:

13 amps

Maximum Pump Starting Current:

78 amps

NOTE: This switch is not recommended for controlling:

- electric loads less than 100 milliamps, 12 VAC

- non-arcing electric loads

NOTE: This switch must be used with pumps that provide integral thermal overload protection.

OTHER INFORMATION

PUMP DOWN is normally open contacts for emptying in water or sewage applications up to 200°F (93°C).

DIRECT WIRING

Units used for direct wiring (without plug) may be used in 125 VAC or 250 VAC applications within specified amp ratings.



Ross Brown Sales Pty Ltd

ABN 28 000 690 362
Phone: 612 9899 2744 Fax: 612 9899 4233
Email: sales@rossbrownsales.com.au
Web: www.rossbrownsales.com.au

SJE
Rhombus®