

TANK ALERT® XT Indoor/Outdoor Alarm (240 VAC)

Versatile, indoor or outdoor liquid level alarm system.

This alarm system monitors liquid levels in lift pump chambers, sump pump basins, holding tanks, sewage, agricultural, and other non-potable water applications.

The Tank Alert® XT indoor/outdoor alarm can serve as a high or low level alarm depending on the float switch model used.

The alarm horn sounds and the red beacon illuminates when a potentially threatening liquid level condition occurs. A "power on" light on the switch indicates power to the alarm panel.



FEATURES

- Enclosure meets Type 3R water-tight standard.
- Automatic alarm reset, horn silence switch, and alarm test switch.
- Alarm horn sounds at 85 decibels at 3 meters (10 feet).
- Alarm system (when installed on separate circuit) operates even if pump circuit fails.
- Complete package includes standard Sensor Float® control switch with 4.57 meters (15 feet) of cable (other lengths available) and mounting clamp.
- Three-year limited warranty.



SPECIFICATIONS

VOLTAGE: 220-240 VAC, 50/60 Hz

ALARM ENCLOSURE: 16.51 cm x 11.43 cm x 7.62 cm (6.5 inch x 4.5 inch x 3 inch), indoor-outdoor, weatherproof, thermo-plastic

AUXILIARY ALARM CONTACTS (OPTIONAL): 240 VAC, 50/60 Hz, 5 amps

TERMINAL BLOCK (OPTIONAL): 240 VAC, 20 amps

ALARM HORN: 82 decibels at 3 meters (10 feet)

FLOAT SWITCH: SJE SignalMaster® control switch with mounting clamp
Cable: 4.57 meters (15 feet) of flexible 18 gauge, 2 conductor SJOW (UL,CSA), water-resistant, chlorinated polyethylene (CPE)
Float: 7.0 cm x 12.3 cm (2.74 inch diameter x 4.83 inch long) high impact corrosion resistant polypropylene for use in sewage and non-potable water up to 60°C (140°F)
Switch: 125/250 VAC, 50/60 Hz, 5 amps

OPTIONS

When ordered with the alarm, this system is available with:

- alternate float switch models for high or low liquid level warning.
- auxiliary dry normally open contacts for easy attachment of remote devices.
- premounted terminal block so enclosure can also be used as a junction box for splicing pump, pump switch, and pump power. Meets NEC standard for junction boxes.
- 1.8 meter (6 feet) power cord and liquid-tight connectors.

Ordering Information

RBS Stock Code	Description
3710492	Tank Alert XT 240V
3710493	Tank Alert XT Incl. Power Lead & Plug
3710495	Tank Alert XT + Terminal Block
3710496	Tank Alert XT + Terminal Block + High Level SignalMaster 5mtr
3710497	Tank Alert XT + Terminal Block + Low Level SignalMaster 5mtr

Accessories

3710499	Cable Weight 800g
---------	-------------------



Ross Brown Sales Pty Ltd

ABN 28 000 690 362
Phone: 612 9899 2744 Fax: 612 9899 4233
Email: sales@rossbrownsales.com.au
Web: www.rossbrownsales.com.au