

ACCESSORIES

Cable Weight, Cable Connectors, Hub Assembly, Cord Seal, and Float Bracket.

CABLE WEIGHT

Provides an accurate pivot point for suspended float switches.

- Gripper teeth on clip an weight channel securely lock float cable into place
- Cable Weight can be adjusted without the use of tools

HOUSING: 0.8 kgs. (1 pound, 12 ounce), 7.1 cm diameter x 8.4 cm long (2.8 inch diameter x 3.3 inch long), impact resistant, non-corrosive, PVC housing for use in liquids up to 60°C (140°F)

CLIP: injection molded acetal plastic

WIRE/CABLE ACCOMMODATED: SJOW, SJTW, 18/2, 18/3, 16/2, 16/3, 14/2, and 14/3



HUB ASSEMBLY

Terminal Adapter.

- Available in 2.54, 3.81, 5.08 cm (1, 1.5, and 2 inch) sizes
- UL Approved and CSA Certified terminal adapter

TERMINAL ADAPTER (HUB): PVC

GASKET: neoprene

LOCK NUT: metal



CORD SEAL

Provides strain relief and a liquid-tight seal.

- Seal 1-3 cables in 5.08 cm (2 inch) terminal adapters
- 2 PVC plugs included (for unused cable positions)
- Ground wire

SEAL: neoprene

WASHERS: stainless steel

NUT AND BOLT: stainless steel


WIRE/CABLE ACCOMMODATED: SJOW, SJTW, 18/2, 18/3, 16/2, 16/3, 14/2, and 14/3



FLOAT BRACKET

Provides convenient installation of float switches.

- Six Float Bracket supports 1-6 floats
- Four Float Bracket supports 1-4 floats
- Can be directly mounted to wall or used with wall mounting device
- Provides convenient location to stow excess float cord
- Supplied with UL Recognized cord strain relief connectors



METAL COMPONENTS: all metal components are made of 300 series stainless steel

STRAIN RELIEF CONNECTORS: accommodate 18/2, 18/3, 16/2, 16/3, SJOW and SJTW cords

CABLE CONNECTORS

Provides strain relief and a liquid-tight seal.

- UL Approved and CSA Certified




ROUND CABLE SPECIFICATIONS

MATERIAL: polyimide flame-resisting, self-extinguishing plastic

O-RING: neoprene plastic

HOLE REQUIREMENT:

NPT threaded OR
clearance holes
(jam nut included)



RCC-8

NPT Hub: 1.27 cm (.50 inch)

Maximum Diameter: 1.22 cm (.480 inch)

Minimum Diameter: .68 cm (.270 inch)

Wire/Cable (AWG) Accommodated:

18/2, 18/3, 18/4, 16/2, 16/4, 14/2, and 14/3

RCC-12

NPT Hub: 1.90 cm (.75 inch)

Maximum Diameter: 1.80 cm (.709 inch)

Minimum Diameter: 1.38 cm (.545 inch)

Wire/Cable (AWG) Accommodated:

14/2, 14/3, 14/4, 12/2, 12/3, 12/4, 10/2
and 10/3

RCC-16

NPT Hub: 2.54 cm (1.0 inch)

Maximum Diameter: 2.49 cm (.98 inch)

Minimum Diameter: 1.80 cm (.71 inch)

Wire/Cable (AWG) Accommodated:

Round cable with outside diameter within
range identified above.


FLAT UF CABLE SPECIFICATIONS

MATERIAL: weather-stabilized thermoplastic

O-RING: neoprene plastic

HOLE REQUIREMENT:

NPT threaded OR
clearance holes
(jam nut included)



UFCC-8

NPT Hub: 1.27 cm (.50 inch)

Maximum: .66 cm x 1.42 cm (.26 inch
x .56 inch) slot

Wire/Cable (AWG) Accommodated:

14/2, 12/2, and 10/2

UFCC-12

NPT Hub: 1.90 cm (.75 inch)

Maximum: .66 cm x 1.42 cm (.26 inch
x .56 inch) slot

Wire/Cable (AWG) Accommodated:

14/3 and 12/3



Ross Brown Sales Pty Ltd

ABN 28 000 690 362

Phone: 612 9899 2744 Fax: 612 9899 4233

Email: sales@rossbrownsales.com.au

Web: www.rossbrownsales.com.au