

SJE SIGNALMASTER® Control Switch

Mechanically-activated, narrow-angle float switch designed to activate pump control panels and alarms.

This narrow-angle sensing device is used to accurately monitor liquid levels in:

- Potable water
- Water
- Sewage applications

The SJE SignalMaster® control switch is not sensitive to rotation.

Normally Open Model (high level)

The control switch turns on (closes) when the float tips slightly **above** horizontal signaling a high level, and turns off (opens) when the float drops slightly below horizontal.

Normally Closed Model (low level)

The control switch turns on (closes) when the float tips slightly **below** horizontal signaling a low level, and turns off (opens) when the float tips slightly above horizontal.



FEATURES

- Passed NSF Standard 61 protocol by an approved Water Quality Association laboratory.
- Mechanically-activated, snap action contacts.
- High impact, corrosion resistant, polypropylene float housing.
- Not sensitive to rotation.
- Control differential of 4 cm (1.5 inches) above or below horizontal.
- UL Listed for use in water and sewage.
- CSA Certified.
- Three-year limited warranty.



SPECIFICATIONS

CABLE: flexible 18 gauge, 2 conductor (UL, CSA) SJOW, water-resistant, (CPE)

FLOAT: 7.0 cm diameter x 12.3 cm long (2.74 inch x 4.83 inch), high impact, corrosion resistant, polypropylene housing for use in sewage and water up to 60°C (140°F)

MAXIMUM WATER DEPTH: 9 meters (30 feet), 90 kPa (13 psi)

ELECTRICAL: 125/250 VAC, 50/60 Hz, 5 amps

NOTE: This switch is not recommended for controlling:

- electric loads less than 100 milliamps, 12 VAC
- non-arcing electric loads

OPTIONS

This switch is available:

- CE Compliant units available upon request.
- for normally open (high level) applications or normally closed (low level) applications.
- in standard cable lengths of 3, 5, 6 or 10 meters and 10, 15, 20, or 30 feet (longer lengths available).
- with two mounting options that allow for flexibility in installation:

Mounting Clamp: for applications where the switch can be attached to a discharge pipe or similar mounting device.

Externally Weighted: for applications where the switch can be suspended from above.



Ross Brown Sales Pty Ltd

ABN 28 000 690 362

Phone: 612 9899 2744 Fax: 612 9899 4233

Email: sales@rossbrownsales.com.au

Web: www.rossbrownsales.com.au

SJE
Rhombus
CONTROLS

PO Box 1708, Detroit Lakes, MN 56502
1-218-847-1317

email: sje@sjerhombus.com

www.sjerhombus.com