

# TANK ALERT® XT Indoor/Outdoor Alarm (240 VAC)

## Versatile, indoor or outdoor liquid level alarm system.

This alarm system monitors liquid levels in lift pump chambers, sump pump basins, holding tanks, sewage, agricultural, and other non-potable water applications.

The Tank Alert® XT indoor/outdoor alarm can serve as a high or low level alarm depending on the float switch model used.

The alarm horn sounds and the red beacon illuminates when a potentially threatening liquid level condition occurs. A "power on" light on the switch indicates power to the alarm panel.



## FEATURES

- Enclosure meets Type 3R water-tight standard.
- Automatic alarm reset, horn silence switch, and alarm test switch.
- Alarm horn sounds at 85 decibels at 3 meters (10 feet).
- Alarm system (when installed on separate circuit) operates even if pump circuit fails.
- Complete package includes standard Sensor Float® control switch with 4.57 meters (15 feet) of cable (other lengths available) and mounting clamp.
- Three-year limited warranty.



## OPTIONS

### When ordered with the alarm, this system is available with:

- alternate float switch models for high or low liquid level warning.
- auxiliary dry normally open contacts for easy attachment of remote devices.
- premounted terminal block so enclosure can also be used as a junction box for splicing pump, pump switch, and pump power. Meets NEC standard for junction boxes.
- 1.8 meter (6 feet) power cord and liquid-tight connectors.

## SPECIFICATIONS

**VOLTAGE:** 220-240 VAC, 50/60 Hz

**ALARM ENCLOSURE:** 16.51 cm x 11.43 cm x 7.62 cm (6.5 inch x 4.5 inch x 3 inch), indoor-outdoor, weatherproof, thermo-plastic

**AUXILIARY ALARM CONTACTS (OPTIONAL):** 240 VAC, 50/60 Hz, 5 amps

**TERMINAL BLOCK (OPTIONAL):** 240 VAC, 20 amps

**ALARM HORN:** 82 decibels at 3 meters (10 feet)

**FLOAT SWITCH:** SJE SignalMaster® control switch with mounting clamp  
**Cable:** 4.57 meters (15 feet) of flexible 18 gauge, 2 conductor SJOW (UL, CSA), water-resistant, chlorinated polyethylene (CPE)  
**Float:** 7.0 cm x 12.3 cm (2.74 inch diameter x 4.83 inch long) high impact corrosion resistant polypropylene for use in sewage and non-potable water up to 60°C (140°F)  
**Switch:** 125/250 VAC, 50/60 Hz, 5 amps

**SJE**  
**Rhombus**  
CONTROLS

PO Box 1708, Detroit Lakes, MN 56502  
1-218-847-1317

email: [sje@sjerhombus.com](mailto:sje@sjerhombus.com)

[www.sjerhombus.com](http://www.sjerhombus.com)



**Ross Brown Sales Pty Ltd**

ABN 28 000 690 362

Phone: 612 9899 2744 Fax: 612 9899 4233

Email: [sales@rossbrownsales.com.au](mailto:sales@rossbrownsales.com.au)

Web: [www.rossbrownsales.com.au](http://www.rossbrownsales.com.au)